



Recessed Linear LED Lighting 30x37

Housing

Eletrostatic powder paint coated aluminum.

Diffuser

Opal diffuser with high transmissivity.

LED

SMD LED with high color rendering index minimum lifetime of 50.000 hours (L70-85°C).

Driver

Constant current output, high efficiency driver.

Option

- Emergency Lighting Kit for 1 or 3 hours period.
- DIM/DALI DIM
- Special design in preferred sizes.


Housing Color







Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Montage Dimens.	Voltage	Weight	Measurements
Recessed Linear 600mm	320305	3000K	980 lm	18W	30x612mm	220VAC	0,45 Kg	
Recessed Linear 600mm	320405	4000K	1030 lm					
Recessed Linear 600mm	320605	6500K	1080 lm					
Recessed Linear 1000mm	320306	3000K	1630 lm	30W	30x1012mm	220VAC	0,76 Kg	
Recessed Linear 1000mm	320406	4000K	1710 lm					
Recessed Linear 1000mm	320606	6500K	1800 lm					
Recessed Linear 1200mm	320307	3000K	1960 lm	36W	30x1212mm	220VAC	0,84 Kg	
Recessed Linear 1200mm	320407	4000K	2050 lm					
Recessed Linear 1200mm	320607	6500K	2160 lm					
Recessed Linear 1500mm	320308	3000K	2450 lm	45W	30x1512mm	220VAC	1,15 Kg	
Recessed Linear 1500mm	320408	4000K	2570 lm					
Recessed Linear 1500mm	320608	6500K	2700 lm					

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X=0 White Y=3 3000K
2 Grey 4 4000K
3 Black 6 6500K