



## Surface Mounted Sterile Ortam Backlight LED Lighting 60x60 - 30x120

### Housing

Eletrostatic powder paint DKP Metal Housing

### Diffuser

Opal diffuser with high transmissivity.

### Glass

Tempered Glass.

### LED

SMD LED with high color rendering index  
minimum lifetime of 50.000 hours (L70-85°C).

### Driver

Constant current output, high efficiency driver.

### Option

- ▶ Emergency Lighting Kit for 1 or 3 hours period.
- ▶ DIM/DALI DIM

### Light Angle



### Light Color



Product Name	Order Code <sup>(2)</sup>	CCT (K)	Luminous Flux <sup>(1)</sup>	Power	Voltage	Weight	Measurements
Surface Mounted Sterile Backlight 60x60	204330	3000K	3885 lm	40W	220VAC	10,00 Kg	
Surface Mounted Sterile Backlight 60x60	204430	4000K	4030 lm				
Surface Mounted Sterile Backlight 60x60	204630	6500K	4175 lm				
Surface Mounted Sterile Backlight 30x120	204342	3000K	3856 lm	40W	220VAC	11,00 Kg	
Surface Mounted Sterile Backlight 30x120	204442	4000K	4000 lm				
Surface Mounted Sterile Backlight 30x120	204642	6500K	4145 lm				

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X= 0 White Y= 3 3000K  
2 Grey 4 4000K  
3 Black 6 6500K