



BA11
LED Bar
Surface Mounted



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP40 Protection
Electrical Safety Class III

Body Color Options



OPTIC

PC Diffuser, Lens
IEC/EN 62471 Photo-Biologic Protection RG0
UGR (CIE Pub.117):21

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



CCT




CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
198~264VAC
50~60Hz
PF>0.95
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



STANDARDS


Luminaire Standarts
Driver Standarts


EN 60598-1 - EN 60598-2-1
-

Surface Mounted

 BA11-AD10 60 LED/m	 9,2mm 14,8mm 1000mm	Power	Lum. Flux	Efficiency	Packaging Sizes	
		14W	641 lm	46 lm/W	Width	- cm
					Length	- cm
					Heigth	- cm
					Amount per ctn.	- pcs.
					Ctn. weighth	- kg
					Deci	-

 BA11-BD10 120 LED/m	 9,2mm 14,8mm 1000mm	Power	Lum. Flux	Efficiency	Packaging Sizes	
		14W	806 lm	55 lm/W	Width	- cm
					Length	- cm
					Heigth	- cm
					Amount per ctn.	- pcs.
					Ctn. weighth	- kg
					Deci	-

 BA11-CD10 168 LED/m	 9,2mm 14,8mm 1000mm	Power	Lum. Flux	Efficiency	Packaging Sizes	
		14W	944 lm	66 lm/W	Width	- cm
					Length	- cm
					Heigth	- cm
					Amount per ctn.	- pcs.
					Ctn. weighth	- kg
					Deci	-

 BA11-DD10 72 LED/m	 9,2mm 14,8mm 1000mm	Power	Lum. Flux	Efficiency	Packaging Sizes	
		14W	853 lm	58 lm/W	Width	- cm
					Length	- cm
					Heigth	- cm
					Amount per ctn.	- pcs.
					Ctn. weighth	- kg
					Deci	-

****The specified luminous flux values may vary by %10.**

ORDER CODE EXPENSION

BA11- BD10- 014 - 8 65 S -9006-PCD8- 2 X X S 20												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACCESSORY	IP
BA11	AD10 BD10 CD10 DD10	014: 14W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K MB: Amber RD: Red GR: Green BL: Blue	S: Standart	9006: Gri	PCD8: PC %80	1: 12V 2: 24V			S: Standart K: İki Uç Kablolu W: IP65 Soketli	20: IP20