



BA15
PC LED Bar
Surface Mounted



HOUSING
Polycarbonate extruded monoblock housing
IP40 Protection
Electrical Safety Class III

Body Color Options

9016
White


OPTIC
PC Diffuser
IEC/EN 62471 Photo-Biologic Protection RG0
UGR (CIE Pub.117):21

Optic Options

120°

LED
SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index
80⁺
Ra>80

CCT

2700K 3000K 4000K 5000K 5700K 6500K Blue Green Red Amber

CONTROL
Rated Input Voltage 220~240VAC
Range of Input Voltage 198~264VAC
Frequency 50~60Hz
Power Factor PF>0.95
Operating Temperature -20°C ~ +50°C
Constant Current LED Driver Over Current Protection (OCP), Over Voltage Protectio (OVP), Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features
24V DC
INPUT

STANDARDS
Luminaire Standarts EN 60598-1 - EN 60598-2-1
Driver Standarts -

BA15
PC LED Bar
Surface Mounted




Table with 3 columns: Power, Lum. Flux, Efficiency. Values: 14W, - lm, - lm/W.

Table with 2 columns: Packaging Sizes, values. Rows: Width, Length, Height, Amount per ctn., Ctn. weight, Deci.




Table with 3 columns: Power, Lum. Flux, Efficiency. Values: 14W, - lm, - lm/W.

Table with 2 columns: Packaging Sizes, values. Rows: Width, Length, Height, Amount per ctn., Ctn. weight, Deci.




Table with 3 columns: Power, Lum. Flux, Efficiency. Values: 14W, - lm, - lm/W.

Table with 2 columns: Packaging Sizes, values. Rows: Width, Length, Height, Amount per ctn., Ctn. weight, Deci.

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

Table with 13 columns: GROUP CODE, BODY CODE, POWER, CRI, CCT, EFFICIENCY, BODY COLOR, OPTIC, CONTROL, DRIVER, KIT, ACSESSORY, IP. Row 1: BA15-BD10-014-865S-9016-0120-2XXS40.