



BA22
LED Bar
Surface Mounted



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP40 Protection
Electrical Safety Class III

Body Color Options



OPTIC

UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



CCT




CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
198~264VAC
50~60Hz
PF>0.95
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



STANDARDS

Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-1
-

BA22 LED Bar Surface Mounted



BA22-AU10
60 LED/m



Power	Lum. Flux	Efficiency
14W	895 lm	63 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-



BA22-BU10
120 LED/m



Power	Lum. Flux	Efficiency
14W	909 lm	63 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-



BA22-CU10
168 LED/m



Power	Lum. Flux	Efficiency
14W	1145 lm	79 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-

****The specified luminous flux values may vary by %10.**

ORDER CODE EXPANSION

BA22-BD10-		014 -		8		65		S		-IPPU -		0120 -		2		X		X		S		65	
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP											
BA22	AU10 BU10 CU10	014: 14W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K MB: Amber RD: Red GR: Green BL: Blue	S: Standart H: Yüksek	IPPU: Poliüretan	0120: 120°	1: 12V 2: 24V			S: Standart K: İki Uç Kablolu W: IP65 Soketli	65: IP65											