




D053
IP65 Wall LED Lighting
GU10



HOUSING
Electrostatic powder paint coated die cast aluminum housing
IP65 Protection
Electrical Safety Class I

Body Color Options



OPTIC
-

LED
-


CONTROL
Rated Input Voltage -
Range of Input Voltage -
Frequency -
Power Factor -
Operating Temperature -
Constant Current LED Driver -


STANDARDS
Luminaire Standarts -
Driver Standarts -

D053

IP65 Wall LED Lighting

GU10

 D053-1070		Power	Lum. Flux	Efficiency	Packaging Sizes	
		GU10	- lm	- lm/W	Width	XX cm
					Length	XX cm
					Height	XX cm
					Amount per ctn.	X pcs.
					Ctn. weight	XX kg
					Deci	X,XX

 D053-2070		Power	Lum. Flux	Efficiency	Packaging Sizes	
		2xGU10	- lm	- lm/W	Width	XX cm
					Length	XX cm
					Height	XX cm
					Amount per ctn.	X pcs.
					Ctn. weight	XX kg
					Deci	X,XX

ORDER CODE EXPENSION

D053-	2070 -	G10 -	X	XX	X	- 9016-	XXXX-	X	X	X	X	65
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
D053	1070 2070	G10: GU10				9016: White 9006: Gray 9005: Black						65: IP65