



GP21

IP65 Landscape

LED Lighting



HOUSING

Electrostatic powder paint coated extruded aluminum housing
 IP66 Protection
 IK09 Impact Protection
 Electrical Safety Class I


Body Color Options



OPTIC

UGR (CIE Pub.117): 21
 IEC/EN 62471 Photo-Biologic Protection RGO

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
 High color rendering (CRI>80)

Color Rendering Index

80⁺
 Ra>80

CCT



CONTROL

Rated Input Voltage 220~240VAC
 Range of Input Voltage 90~305VAC
 Frequency 50~60Hz
 Power Factor PF>0.95
 Operating Temperature -40°C ~ +60°C
 Constant Current LED Driver

Additional Features

0-10V
 0-10V Prog.

Over Current Protection (OCP), Over Voltage Protectio (OVP),
 Short Circuit Protection (SCP), Over Temperature Protection (OTP)


STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-3
 Driver Standarts LVD (EN 61347-1, EN 61347-2-13)
 EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

GP21

IP65 Landscape

LED Lighting


 <p>GP21-0052 50cm</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>24W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	24W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
24W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>GP21-0082 80cm</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>24W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	24W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
24W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>GP21-0102 1m</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>24W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	24W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
24W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>GP21-0302 3m</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>2x36W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	2x36W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
2x36W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>GP21-0402 4m</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>2x36W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	2x36W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
2x36W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>GP21-0502 5m</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>4x36W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	4x36W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
4x36W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>GP21-0602 6m</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>4x36W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	4x36W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
4x36W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

GP21- 0402 - 036 - 8 40 S - 9005-0090- V S S S 66

GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACCESSORY	IP
GP21	0052 0082 0102 0302 0402 0502 0602	012: 12W 036: 36W 072: 72W	8: 80	27: 2700K 30: 3000K 40: 4000K 50: 5000K 65: 6500K	S: Standart	9006: Gray 7016: Anthracite 9005: Black	0030: 30° 0060: 60° 0090: 90° OV49: 35°-85° AS00: Asymmetric	V: 0-10V Prog.	S: LAMPTIME	S: Standart	S: Standart	66: IP66



GP21

IP65 Landscape

LED Lighting



HOUSING

Electrostatic powder paint coated extruded aluminum housing
 IP66 Protection
 IK09 Impact Protection
 Electrical Safety Class I


Body Color Options



OPTIC

UGR (CIE Pub.117): 21
 IEC/EN 62471 Photo-Biologic Protection RGO

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
 High color rendering (CRI>80)

Color Rendering Index

80⁺
 Ra>80

CCT



CONTROL

Rated Input Voltage 220~240VAC
 Range of Input Voltage 90~305VAC
 Frequency 50~60Hz
 Power Factor PF>0.95
 Operating Temperature -40°C ~ +60°C
 Constant Current LED Driver

Additional Features

0-10V
 0-10V Prog.

Over Current Protection (OCP), Over Voltage Protectio (OVP),
 Short Circuit Protection (SCP), Over Temperature Protection (OTP)

STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-3
 Driver Standarts LVD (EN 61347-1, EN 61347-2-13)
 EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

GP21

IP65 Landscape

LED Lighting

 <p>GP21-0051 50cm</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>12W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	12W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
12W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>GP21-0081 80cm</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>12W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	12W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
12W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>GP21-0101 1m</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>12W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	12W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
12W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>GP21-0301 3m</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>36W</td> <td>4167 lm</td> <td>112 lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	36W	4167 lm	112 lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
36W	4167 lm	112 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>GP21-0401 4m</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>36W</td> <td>4167 lm</td> <td>112 lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	36W	4167 lm	112 lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
36W	4167 lm	112 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>GP21-0501 5m</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>2x36W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	2x36W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
2x36W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>GP21-0601 6m</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>2x36W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	2x36W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
2x36W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

GP21- 0401 - 036 - 8 40 S - 9005-0090- V S S S 66

GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACCESSORY	IP
GP21	0051 0081 0101 0301 0401 0501 0601	012: 12W 036: 36W 072: 72W	8: 80	27: 2700K 30: 3000K 40: 4000K 50: 5000K 65: 6500K	S: Standart	9006: Gray 7016: Anthracite 9005: Black	0030: 30° 0060: 60° 0090: 90° OV49: 35°-85° AS00: Asymmetric	V: 0-10V Prog.	S: LAMPTIME	S: Standart	S: Standart	66: IP66