




GR24

IP65 Landscape

LED Lighting



HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP65 Protection
IK08 Impact Protection
Electrical Safety Class I


Body Color Options



OPTIC

UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index

80⁺
Ra>80

CCT



CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
90~305VAC
50~60Hz
PF>0.95
-40°C ~ +60°C

Additional Features

0-10V
0-10V Prog.

Over Current Protection (OCP), Over Voltage Protection (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

STANDARDS

Luminaire Standards
Driver Standards

EN 60598-1 - EN 60598-2-3
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)


GR24

IP65 Landscape

LED Lighting



GR24-048S



Power	Lum. Flux	Efficiency	Packaging Sizes	
60W	5527 lm	92 lm/W	Width	- cm
90W	8100 lm	90 lm/W	Length	- cm
			Height	- cm
			Amount per ctn.	- pcs.
			Ctn. weight	- kg
			Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

GR24- 048S- 090 - 8 40 S - 9005-0120- V S S S 65												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
GR24	048S	060: 60W 090: 90W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9006: Gri 7016: Antrasit 9005: Siyah	0030: 30° 0060: 60° 0090: 90° 0V49: 35°-85° AS00: Asimetrik	V: 0-10V Prog.	S: LAMPTIME	S: Standart	S: Standart	65: IP65