



GR27

IP65 Landscape

LED Lighting



HOUSING
Electrostatic powder paint coated extruded aluminum housing
IP66 Protection
IK08 Impact Protection
Electrical Safety Class I

Body Color Options

9006
Gray

7016
Anthracite

9005
Black

OPTIC
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options

120°

LED
COB LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index

80⁺
Ra>80

CCT

2700K

3000K

4000K

5000K

5700K

6500K

CONTROL
Rated Input Voltage 220~240VAC
Range of Input Voltage 90~305VAC
Frequency 50~60Hz
Power Factor PF>0.95
Operating Temperature -40°C ~ +60°C
Constant Current LED Driver

Additional Features

ON/OFF

STANDARDS
Luminaire Standarts EN 60598-1 - EN 60598-2-3
Driver Standarts LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

GR27
IP65 Landscape
LED Lighting

		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>12W</td><td>- lm</td><td>- lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	12W	- lm	- lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigh</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigh</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigh	- cm	Amount per ctn.	- pcs.	Ctn. weigh	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
12W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigh	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigh	- kg																						
Deci	-																						
GR27-0051 50 cm																							

		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>12W</td><td>- lm</td><td>- lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	12W	- lm	- lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigh</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigh</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigh	- cm	Amount per ctn.	- pcs.	Ctn. weigh	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
12W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigh	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigh	- kg																						
Deci	-																						
GR27-0081 80 cm																							

		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>12W</td><td>- lm</td><td>- lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	12W	- lm	- lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigh</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigh</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigh	- cm	Amount per ctn.	- pcs.	Ctn. weigh	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
12W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigh	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigh	- kg																						
Deci	-																						
GR27-0101 1 m																							

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

GR27- 0081 - 012 - 8 40 S - 9005-0120 - O S S S 66												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
GR27	0051 0081 0101	012: 12W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9006: Gray 7016: Anthracite 9005: Black	0120: 120°	O: ON-OFF	S: LAMPTIME	S: Standart	S: Standart	66: IP66