



GR30

IP66 Landscape

LED Lighting



GROUND



CE



VOLTAGE



PROTECT.



IMPACT



CLASS I



Ta



MADE IN
TÜRKIYE

HOUSING

Electrostatic powder paint coated extruded aluminum housing

IP66 Protection

IK09 Impact Protection

Electrical Safety Class I

Body Color Options



9006
Gray



7016
Anthracite



9005
Black

OPTIC

UGR (CIE Pub.117): 21

IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



120°

LED

COB LED with a minimum lifetime of 100.000 hours

High color rendering (CRI>80)

Color Rendering Index



Ra>80

CCT



2700K



3000K



4000K



5000K



5700K



6500K

CONTROL

Rated Input Voltage

220~240VAC

Range of Input Voltage

90~305VAC

Frequency

50~60Hz

Power Factor

PF>0.95

Operating Temperature

-40°C ~ +60°C

Constant Current LED Driver

Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



ON/OFF

STANDARDS

Luminaire Standarts

EN 60598-1 - EN 60598-2-3

Driver Standarts

LVD (EN 61347-1, EN 61347-2-13)

EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

GR30


IP66 Landscape

LED Lighting



GR30-1303

30 cm




Power	Lum. Flux	Efficiency
12W	- lm	- lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Heigh	- cm
Amount per ctn.	- pcs.
Ctn. weigh	- kg
Deci	-



GR30-1305

50 cm




Power	Lum. Flux	Efficiency
12W	- lm	- lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Heigh	- cm
Amount per ctn.	- pcs.
Ctn. weigh	- kg
Deci	-



GR30-1308

80 cm



Power	Lum. Flux	Efficiency
12W	- lm	- lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Heigh	- cm
Amount per ctn.	- pcs.
Ctn. weigh	- kg
Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

GR30- 1305 - 012 - 8 40 S - 9005-0120 - O S S S 66												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
GR30	1303 1305 1308	012: 12W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9006: Gray 7016: Anthracite 9005: Black	0120: 120°	O: ON-OFF	S: LAMPTIME	S: Standart	S: Standart	66: IP66