




IL10

IP66 Waterproof

LED Lighting



HOUSING

ABS Housing
IP66 Protection
IK07 Impact Protection
Electrical Safety Class I

Body Color Options



9006
Gray

OPTIC

PC Diffuser
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options




120°

LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



Ra>80

Ra>90
(Optional)

CCT



2700K

3000K

4000K

5000K

5700K


6500K

CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264VAC
50~60Hz
PF>0.95
-20°C ~ +50°C

Additional Features



ON/OFF

DIM

Emergency
Lighting

Corridor
Func.

STANDARDS

Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-1
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

LED Lighting



Power	Lum. Flux	Efficiency
20W	2092 lm	108 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-



Power	Lum. Flux	Efficiency
40W	4279 lm	114 lm/W
54W	5322 lm	101 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-



Power	Lum. Flux	Efficiency
60W	6326lm	106 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

IL10 - 0120 - 040 - 8 40 S -9006-0120- 0 S S S 66

GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACCESSORY	IP
IL10	0060	020: 20W	8: 80	27: 2700K	S: Standard	9006: Gri	0120: 120°	O: ON-OFF	S: LAMPTIME	S: Standard 3: 3 Hours Kit	S: Standard	66: IP66
	0120	040: 40W	9: 90	30: 3000K	H: High			D: DALI				
	0150	054: 54W	40: 4000K	C: Smart Sens.								
		060: 60W	50: 5000K 65: 6500K	W: Smart TW R: Smart RGB								