




IL15

IP65 Low Bay

Aluminum LED Lighting



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP65 Protection
Electrical Safety Class I

Body Color Options



OPTIC

PC Diffuser
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0


Optic Options




LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index




CCT



CONTROL

Rated Input Voltage 220~240VAC
Range of Input Voltage 176~264VAC
Frequency 50~60Hz
Power Factor PF>0.95
Operating Temperature -20°C ~ +50°C
Constant Current LED Driver

Additional Features




STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-1
Driver Standarts LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

IL15
IP65 Waterproof
Aluminum LED Lighting



IL15-0060




Power	Lum. Flux	Efficiency
18W	1847 lm	91 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-



IL15-0120




Power	Lum. Flux	Efficiency
36W	3987 lm	105 lm/W
54W	5046 lm	93 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-



IL15-0150



Power	Lum. Flux	Efficiency
54W	4989 lm	95 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

IL15 - 0120 - 040 - 8 40 S - 9016-0120- O S S S 65												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
IL15	0060 0120 0150	018: 18W 036: 36W 054: 54W	8: 80 9: 90	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9016: White 7016: Anthracite 9005: Black	0120: 120°	O: ON-OFF D: DALI C: Smart Sens. W: Smart TW R: Smart RGB	S: LAMPTIME	S: Standart 3: 3 Hours Kit	S: Standart	65: IP65