



ML43

Magnet LED Lighting

Suspended



TRACK



CE



VOLTAGE



PROTECT.



CLASS III



Ta



MADE IN
TÜRKİYE

HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP20 Protection
Electrical Safety Class III

Body Color Options



9005
Black

OPTIC

Lens
UGR (CIE Pub.117):11
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



38°

LED

Minimum 100.000 saat ömürlü COB LED
High color rendering index (CRI>80)

Color Rendering Index

80⁺

Ra>80

CCT



2700K



3000K



4000K



5000K



5700K



6500K

CONTROL

Rated Input Voltage 48VDC
Range of Input Voltage -
Frequency -
Power Factor -
Operating Temperature -20°C ~ +50°C
Constant Current LED Driver

Additional Features



ON/OFF

Overload Protection (OLP), Overvoltage Protection (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-1
Driver Standarts -

ML43

Magnet LED Lighting

Suspended



Power	Lum. Flux	Efficiency	Packaging Sizes	
12W	434 lm	28 lm/W	Width	- cm
			Length	- cm
			Height	- cm
			Amount per ctn.	- pcs.
			Ctn. weight	- kg
			Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

ML43-	4P30-	012	-	8	40	S	-	9005-	0038-	0	S	S	S	20
GROUP CODE	BODY CODE	POWER		CRI	CCT	EFFICIENCY		BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
ML43	4P30	012: 12W		8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart		9005: Black	0038: 38°	0: ON-OFF	S: LAMPTIME	S: Standart	S: Standart	20: IP20