



OW12
IP67 Wallwasher
LED Lighting



HOUSING
Electrostatic powder paint coated extruded aluminum housing
IP67 Protection
Electrical Safety Class I

Body Color Options



9006
Gray

OPTIC
PMMA Lens
UGR (CIE Pub.117):9
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



15°



30°



45°



Asymmetric

LED
SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>70)

Color Rendering Index



70⁺

Ra>70

CCT



2700K



3000K



4000K



5000K



5700K



6500K



Green



Blue



Red



Amber

CONTROL
Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264VAC
50~60Hz
PF>0.95
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



ON/OFF

STANDARDS
Luminaire Standarts
Driver Standarts
EN 60598-1 - EN 60598-2-1
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

OW12
IP67 Wallwasher
LED Lighting

		Power	Lum. Flux	Efficiency	Packaging Sizes	
		2x6W	1386 lm	116 lm/W	Width	- cm
		Power	Lum. Flux	Efficiency	Packaging Sizes	
		2x12W	3177 lm	120 lm/W	Width	- cm
		Power	Lum. Flux	Efficiency	Packaging Sizes	
		2x18W	4611 lm	117 lm/W	Width	- cm
		Power	Lum. Flux	Efficiency	Packaging Sizes	
		2x24W	7058 lm	133 lm/W	Width	- cm
		Power	Lum. Flux	Efficiency	Packaging Sizes	
		2x30W	7883 lm	134 lm/W	Width	- cm
		Power	Lum. Flux	Efficiency	Packaging Sizes	
		2x36W	9162 lm	125 lm/W	Width	- cm

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

OW10- 0090 - 060 - 8 65 S -9006- 0045- 0 S S S 67												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
OW10	0018	012: 12W	8: 80	27: 2700K	S: Standart	9006: Gray	0015: 15°	0: ON-OFF	S: LAMPTIME	S: Standart	S: Standart	67: IP67
	0036	012: 24W		30: 3000K			0030: 30°					
	0054	018: 18W		40: 4000K			0045: 45°					
	0072	036: 36W		65: 6500K			AS00: Asymmetric					
	0090	048: 48W		MB: Amber								
	0107	060: 60W		RD: Red								
		072: 72W		GR: Green								
				BL: Blue								