




PH11

IP65 Sterile Backlight Panel LED Lighting

Indirect Recessed



HOUSING
Electrostatic powder paint coated metal housing
IP65 Protection
Electrical Safety Class I

Body Color Options

9016
White

OPTIC
PS diffuser with high transmissivity
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0


Optic Options

POLYSTYRENE

LED
SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index

Ra>80

CCT

2700K 3000K 4000K 5000K 5700K 6500K

CONTROL
Rated Input Voltage 220~240VAC
Range of Input Voltage 176~264 VAC
Frequency 50~60Hz
Power Factor PF>0.60 (P≤25W) / PF>0.95 (P≥25W)
Operating Temperature -20°C ~ +50°C
Constant Current LED Driver Over Current Protection (OCP), Over Voltage Protectio (OVP), Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features

ON/OFF

DIM

Emergency Lighting

STANDARDS
Luminaire Standarts EN 60598-1 - EN 60598-2-2
Driver Standarts LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)


PH11

IP65 Sterile Backlight Panel

LED Lighting Indirect Recessed



PH11-6060



Power	Lum. Flux	Efficiency
40W	2013 lm	55 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

PH11	-	6060	-	040	-	8	65	S	-	9016	-	0120	-	0	S	S	S	65
GROUP CODE		BODY CODE		POWER		CRI	CCT	EFFICIENCY		BODY COLOR		OPTIC		CONTROL	DRIVER	KIT	ACSESSORY	IP
PH11		6060		020: 20W 040: 40W		8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart		9016: White		0120:120°		0: ON-OFF D: Dali	S: LAMPTIME	S: Standart 3: 3 Hours Kit	S: Standart	65: IP65