



Mirror Type Aluminum LED Lighting Fixture

Housing

Eloxal coated extruded aluminum Housing.

Diffuser

Polycarbonate Opal Diffuser.

LED

SMD LED with high color rendering index minimum lifetime of 50.000 hours (L70-85°C).

Driver

Driver with constant current output.

Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Voltage	Weight	Measurements
Mirror Type Aluminum 600mm	301383	3000K	1385 lm	15W	220VAC	0,20 Kg	600mm
Mirror Type Aluminum 600mm	301483	4000K	1430 lm				
Mirror Type Aluminum 600mm	301683	6500K	1550 lm				
Mirror Type Aluminum 900mm	301384	3000K	2190 lm	24W	220VAC	0,28 Kg	900mm
Mirror Type Aluminum 900mm	301484	4000K	2255 lm				
Mirror Type Aluminum 900mm	301684	6500K	2370 lm				
Mirror Type Aluminum 1200mm	301385	3000K	2950 lm	30W	220VAC	0,37 Kg	1200mm
Mirror Type Aluminum 1200mm	301485	4000K	3040 lm				
Mirror Type Aluminum 1200mm	301685	6500K	3200 lm				

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X= 0 White Y= 3 3000K
 2 Grey 4 4000K
 3 Black 6 6500K