



## LED Street Lighting IP66

### Housing

Electrostatic powder paint coated die cast aluminum housing.

### Glass

Tempered Glass IK08.

### LED

3030 outdoor Mid Power LED with high color rendering index with minimum lifetime of  $\geq 54.000$  hours.

### Driver

Constant current output, high efficiency driver.

### Option

- ▶ 30° - 60° - 90° Asymmetric Lens
- ▶ Programmable DIM
- ▶ 0-10VDIM
- ▶ PWM



Product Name	Order Code	Power(W)	CCT(K)	Luminous Flux (lm)	CRI	Voltage V	Weight
Yol ve Cadde Aydınlatması	801305	100W	3000K	11600 lm	>70	220VAC	4,9 Kg
Yol ve Cadde Aydınlatması	801405	100W	4000K	12500 lm	>70	220VAC	4,9 Kg
Yol ve Cadde Aydınlatması	801605	100W	6500K	13500 lm	>70	220VAC	4,9 Kg
Yol ve Cadde Aydınlatması	801301	125W	3000K	14700 lm	>70	220VAC	4,9 Kg
Yol ve Cadde Aydınlatması	801401	125W	4000K	15700 lm	>70	220VAC	4,9 Kg
Yol ve Cadde Aydınlatması	801601	125W	6500K	16500 lm	>70	220VAC	4,9 Kg
Yol ve Cadde Aydınlatması	801304	150W	3000K	16700 lm	>70	220VAC	4,9 Kg
Yol ve Cadde Aydınlatması	801404	150W	4000K	17500 lm	>70	220VAC	4,9 Kg
Yol ve Cadde Aydınlatması	801604	150W	6500K	18500 lm	>70	220VAC	4,9 Kg

