



## Recessed COB LED Downlight

### Housing

Electrostatic powder paint coated die cast aluminum housing.

### Reflector

►High purity anodized aluminum.

### Reflector

►15° - 30° - 45° - 60°.

### LED

≥50.000 hours COB LED with high color rendering index.

### Driver

Constant current output, high efficiency driver.

### Option

- Emergency Lighting Kit for 1 or 3 hours period.
- DIM / DALI DIM.



Product Name	Order Code	Power(W)	CCT(K)	Luminous Flux (lm)	CRI	Voltage V	Montage Dimens.(mm)	Weight
Recessed COB LED Downlight	240330	20W	3000K	1800 lm	>80	220VAC	Ø175mm	1,42 Kg
Recessed COB LED Downlight	240430	20W	4000K	1929 lm	>80	220VAC	Ø175mm	1,42 Kg
Recessed COB LED Downlight	240630	20W	6500K	2079 lm	>80	220VAC	Ø175mm	1,42 Kg
Recessed COB LED Downlight	240331	30W	3000K	2800 lm	>80	220VAC	Ø175mm	1,42 Kg
Recessed COB LED Downlight	240431	30W	4000K	2909 lm	>80	220VAC	Ø175mm	1,42 Kg
Recessed COB LED Downlight	240631	30W	6500K	3000 lm	>80	220VAC	Ø175mm	1,42 Kg
Recessed COB LED Downlight	240332	40W	3000K	3175 lm	>80	220VAC	Ø175mm	1,42 Kg
Recessed COB LED Downlight	240432	40W	4000K	3658 lm	>80	220VAC	Ø175mm	1,42 Kg
Recessed COB LED Downlight	240632	40W	6500K	3880 lm	>80	220VAC	Ø175mm	1,42 Kg

