

Recessed COB LED Downlight

Housing

Electrostatic powder paint coated die cast aluminum housing.

Reflector

►High purity anodized aluminum.

LED

≥50.000 hours COB LED with high color rendering index, L70 Performance.

Driver

Costant current output, high efficiency.

Option

- Emergency Lighting Kit for 1 or 3 hours period.
- DIM / DALI DIM.



Product Name	Order Code	Power(W)	CCT(K)	Luminous Flux (lm)	CRI	Voltage V	Montage Dimens.(mm)	Weight
Recessed COB LED Downlight	240301	20W	3000K	1800 lm	>80	220VAC	Ø110 mm	0,82 Kg
Recessed COB LED Downlight	240401	20W	4000K	1870 lm	>80	220VAC	Ø110 mm	0,82 Kg
Recessed COB LED Downlight	240601	20W	6500K	1935 lm	>80	220VAC	Ø110 mm	0,82 Kg
Recessed COB LED Downlight	240302	30W	3000K	2755 lm	>80	220VAC	Ø145 mm	0,90 Kg
Recessed COB LED Downlight	240402	30W	4000K	2860 lm	>80	220VAC	Ø145 mm	0,90 Kg
Recessed COB LED Downlight	240602	30W	6500K	2960 lm	>80	220VAC	Ø145 mm	0,90 Kg

