



## Recessed COB LED Downlight

### Housing

Electrostatic powder paint coated die cast aluminum housing.

### Reflector

►High purity anodized aluminum

### Reflector

►15° - 30°.

### LED

≥50.000 hours COB LED with high color rendering index.

### Driver

Constant current output, high efficiency driver.

### Option

- Emergency Lighting Kit for 1 or 3 hours period.
- DIM / DALI DIM.



Product Name	Order Code	Power(W)	CCT(K)	Luminous Flux (lm)	CRI	Voltage V	Montage Dimens.(mm)	Weight
Recessed COB LED Downlight	240389	20W	3000K	1800 lm	>80	220VAC	Ø140 mm	0,82 Kg
Recessed COB LED Downlight	240489	20W	4000K	1929 lm	>80	220VAC	Ø140 mm	0,82 Kg
Recessed COB LED Downlight	240689	20W	6500K	2079 lm	>80	220VAC	Ø140 mm	0,82 Kg
Recessed COB LED Downlight	240390	30W	3000K	2800 lm	>80	220VAC	Ø140 mm	0,90 Kg
Recessed COB LED Downlight	240490	30W	4000K	2909 lm	>80	220VAC	Ø140 mm	0,90 Kg
Recessed COB LED Downlight	240690	30W	6500K	3000 lm	>80	220VAC	Ø140 mm	0,90 Kg

