



Recessed COB LED Downlight Lighting

Housing

Electrostatic powder paint coated die cast aluminum housing.

Reflector

High purity anodized aluminum.

LED

≥100.000 hours COB LED with high color rendering index.

Driver

Constant current output, high efficiency driver.

Option

- ▶ Emergency Lighting kit for 1 or 3 hours period.
- ▶ DIM/DALI DIM


Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Montage Dimens.	Voltage	Weight	Measurements
Recessed COB Downlight	740339	3000K	500 lm	8W	Ø100mm	220VAC	0,42 Kg	
Recessed COB Downlight	740439	4000K	600 lm					
Recessed COB Downlight	740639	6500K	640 lm					

(1) The specified luminous flux values may vary by %10.

(2) 32XY42 X=0 White Y=3 3000K
 2 Grey 4 4000K
 3 Black 6 6500K



Recessed COB LED Downlight Lighting

Housing

Electrostatic powder paint coated die cast aluminum housing.

Reflector

High purity anodized aluminum.

LED

≥100.000 hours COB LED with high color rendering index.

Driver

Constant current output, high efficiency driver.

Option

- ▶ Emergency Lighting kit for 1 or 3 hours period.
- ▶ DIM/DALI DIM


Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Montage Dimens.	Voltage	Weight	Measurements
Recessed COB Downlight	740340	3000K	1200 lm	2x8W	100x220mm	220VAC	0,80 Kg	
Recessed COB Downlight	740440	4000K	1300 lm					
Recessed COB Downlight	740640	6500K	1340 lm					

(1) The specified luminous flux values may vary by %10.

(2) 32XY42 X=0 White Y=3 3000K
 2 Grey 4 4000K
 3 Black 6 6500K