



Recessed COB LED Downlight Lighting

Housing

Electrostatic powder paint coated die cast aluminum housing.

Reflector

High purity anodized aluminum.

LED

≥100.000 hours COB LED with high color rendering index.

Driver

Constant current output, high efficiency driver.

Option

- ▶ Emergency Lighting kit for 1 or 3 hours period.
- ▶ DIM/DALI DIM

Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Montage Dimens.	Voltage	Weight	Measurements
Recessed COB Downlight	350311	3000K	1140 lm	10W	Ø90mm	220VAC	1,20 Kg	 75mm Ø100mm
Recessed COB Downlight	350411	4000K	1150 lm					
Recessed COB Downlight	350611	6500K	1160 lm					
Recessed COB Downlight	350312	3000K	1810 lm	20W	Ø130mm	220VAC	1,20 Kg	 90mm Ø140mm
Recessed COB Downlight	350412	4000K	2050 lm					
Recessed COB Downlight	350612	6500K	2300 lm					
Recessed COB Downlight	350313	3000K	2700 lm	30W	Ø170mm	220VAC	1,20 Kg	 112mm Ø185mm
Recessed COB Downlight	350413	4000K	2780 lm					
Recessed COB Downlight	350613	6500K	2900 lm					
Recessed COB Downlight	350314	3000K	3260 lm	40W	Ø200mm	220VAC	1,20 Kg	 128mm Ø230mm
Recessed COB Downlight	350414	4000K	3450 lm					
Recessed COB Downlight	350614	6500K	3700 lm					

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X=0 White Y=3 3000K
 2 Grey 4 4000K
 3 Black 6 6500K