



Track LED Lighting

Housing

Electrostatic powder paint coated die cast aluminum housing.

Reflector

High purity anodized aluminum reflector.

LED

≥100.000 hours COB LED with high color rendering index.

Driver

Constant current output, high efficiency driver.


Track Adaptor

- ▶ Single Phase (2 Lines)
- ▶ Three Phase (4 Lines)
- ▶ DALI

Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Voltage	Weight	Measurements
Track LED Lighting	280378-M	3000K	1800 lm	20W	220VAC	1,30 Kg	
Track LED Lighting	280478-M	4000K	1929 lm				
Track LED Lighting	280678-M	6500K	2079 lm				
Track LED Lighting	280379-M	3000K	2800 lm	30W	220VAC	1,30 Kg	
Track LED Lighting	280479-M	4000K	2909 lm				
Track LED Lighting	280679-M	6500K	3000 lm				
Track LED Lighting	280343-M	3000K	3175 lm	40W	220VAC	1,30 Kg	
Track LED Lighting	280443-M	4000K	3658 lm				
Track LED Lighting	280643-M	6500K	3880 lm				

(1) The specified luminous flux values may vary by %10.

(2) 32XY42 X=0 White Y=3 3000K
 2 Grey 4 4000K
 3 Black 6 6500K