



## Decorative Suspended LED Lighting 80x80

### Housing

Eletrostatic powder paint coated aluminum.

### Diffuser

Opal diffuser with high transmissivity.

### LED

SMD LED with high color rendering index minimum lifetime of 100.000 hours (L70-85°C).

### Driver

Constant current output, high efficiency driver.

### Option

- ▶ Emergency Lighting Kit for 1 or 3 hours period.
- ▶ DIM/DALI DIM
- ▶ Surface Mounted


### Housing Color





### Light Angle



### Light Color



Product Name	Order Code <sup>(2)</sup>	CCT (K)	Luminous Flux <sup>(1)</sup>	Power	Voltage	Weight	Measurements
Decorative Suspended Lighting 400mm	290321	3000K	1710lm	30W	220VAC	2,15 Kg	
Decorative Suspended Lighting 400mm	290421	4000K	1800lm				
Decorative Suspended Lighting 400mm	290621	6500K	1890lm				
Decorative Suspended Lighting 600mm	290322	3000K	2775lm	45W	220VAC	3,20 Kg	
Decorative Suspended Lighting 600mm	290422	4000K	2925lm				
Decorative Suspended Lighting 600mm	290622	6500K	3070lm				
Decorative Suspended Lighting 800mm	290323	3000K	3700lm	60W	220VAC	4,25 Kg	
Decorative Suspended Lighting 800mm	290423	4000K	3900lm				
Decorative Suspended Lighting 800mm	290623	6500K	4095lm				
Decorative Suspended Lighting 1000mm	290324	3000K	4630 lm	75W	220VAC	5,33 Kg	
Decorative Suspended Lighting 1000mm	290424	4000K	4875lm				
Decorative Suspended Lighting 1000mm	290624	6500K	5115lm				
Decorative Suspended Lighting 1200mm	290325	3000K	5550lm	90W	220VAC	6,42 Kg	
Decorative Suspended Lighting 1200mm	290425	4000K	5850lm				
Decorative Suspended Lighting 1200mm	290625	6500K	6140lm				

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X=0 White Y=3 3000K  
2 Grey 4 4000K  
3 Black 6 6500K