




LD19

Decorative LED Lighting


Rectangle



HOUSING

Electrostatic powder paint coated extruded aluminum housing
 IP20 Protection
 Electrical Safety Class I

Body Color Options



OPTIC

PS diffuser with high transmissivity
 UGR (CIE Pub.117):21
 IEC/EN 62471 Photo-Biologic Protection RGO

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
 High color rendering (CRI>80)

Color Rendering Index




CCT



CONTROL

Rated Input Voltage 220~240VAC
 Range of Input Voltage 176~264VAC
 Frequency 50~60Hz
 Power Factor PF>0.95
 Operating Temperature -20°C ~ +50°C
 Constant Current LED Driver

Additional Features









Overload Protection (OLP), Overvoltage Protection (OVP),
 Short Circuit Protection (SCP), Over Temperature Protection (OTP)

STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-1
 Driver Standarts LVD (EN 61347-1, EN 61347-2-13)
 EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

LD19

Decorative LED Lighting Rectangle

 <p>LD19-0100</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>60W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	60W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
60W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>LD19-0120</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>75W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	75W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
75W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
 <p>LD19-0150</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>90W</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	90W	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
90W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						

**The specified luminous flux values may vary by %10.

ORDER CODE EXPANSION

LD19- 0120 - 075 - 8 40 S - 9005-0120- 0 S S S 20

GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACCESSORY	IP
LD19	0100 0120 0150	060: 60W 075: 75W 090: 90W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9016: White 9006: Gray 9005: Black	0120: 120°	O: ON-OFF D: Dali W: Smart TW	S: LAMPTIME	S: Standart	S: Standart P: Suspended	20: IP20