



## Magnet LED Lighting With Adjustable Diffuser

### Housing

Electrostatic powder paint coated die cast aluminum housing

### Diffuser

Opal diffuser with high transmissivity.

### LED

SMD LED with a minimum lifetime of 100.000 hours

### Driver

Constant current output, high efficiency driver


### Housing Color



### Light Angle



### Light Color



Product Name	Order Code <sup>(2)</sup>	CCT (K)	Luminous Flux <sup>(1)</sup>	Power	Voltage	Weight	Measurements
Magnet With Adjustable Diffuser 300mm	783331	3000K	950lm	12W	48V DC	0,17 Kg	300mm
Magnet With Adjustable Diffuser 300mm	783431	4000K	970lm				
Magnet With Adjustable Diffuser 300mm	783631	6500K	980lm				
Magnet With Adjustable Diffuser 600mm	783332	3000K	1910lm	24W	48V DC	0,23 Kg	600mm
Magnet With Adjustable Diffuser 600mm	783432	4000K	1950lm				
Magnet With Adjustable Diffuser 600mm	783632	6500K	1970lm				

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X= 0 White Y= 3 3000K  
2 Grey 4 4000K  
3 Black 6 6500K