




OF10

IP65 SMD

LED Floodlight



HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP65 Protection
Electrical Safety Class I

Body Color Options



OPTIC

Tempered Glass
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index




CCT



CONTROL

Rated Input Voltage 220~240VAC
Range of Input Voltage 90~305VAC
Frequency 50~60Hz
Power Factor PF>0.95
Operating Temperature -40°C ~ +60°C
Constant Current LED Driver

Additional Features



Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)









STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-5
Driver Standarts LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

OF10

IP65 SMD

LED Floodlight

 <p>OF10-020S</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>30W</td> <td>3389 lm</td> <td>114 lm/W</td> </tr> <tr> <td>50W</td> <td>5381 lm</td> <td>122 lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	30W	3389 lm	114 lm/W	50W	5381 lm	122 lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																								
30W	3389 lm	114 lm/W																								
50W	5381 lm	122 lm/W																								
Packaging Sizes																										
Width	- cm																									
Length	- cm																									
Height	- cm																									
Amount per ctn.	- pcs.																									
Ctn. weight	- kg																									
Deci	-																									
 <p>OF10-030M</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>70W</td> <td>8972 lm</td> <td>124 lm/W</td> </tr> <tr> <td>100W</td> <td>11694 lm</td> <td>129 lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	70W	8972 lm	124 lm/W	100W	11694 lm	129 lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																								
70W	8972 lm	124 lm/W																								
100W	11694 lm	129 lm/W																								
Packaging Sizes																										
Width	- cm																									
Length	- cm																									
Height	- cm																									
Amount per ctn.	- pcs.																									
Ctn. weight	- kg																									
Deci	-																									
 <p>OF10-040L</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>150W</td> <td>18025 lm</td> <td>124 lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	150W	18025 lm	124 lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-			
Power	Lum. Flux	Efficiency																								
150W	18025 lm	124 lm/W																								
Packaging Sizes																										
Width	- cm																									
Length	- cm																									
Height	- cm																									
Amount per ctn.	- pcs.																									
Ctn. weight	- kg																									
Deci	-																									
 <p>OF10-05XL</p>		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>200W</td> <td>22595 lm</td> <td>123 lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	200W	22595 lm	123 lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-			
Power	Lum. Flux	Efficiency																								
200W	22595 lm	123 lm/W																								
Packaging Sizes																										
Width	- cm																									
Length	- cm																									
Height	- cm																									
Amount per ctn.	- pcs.																									
Ctn. weight	- kg																									
Deci	-																									

**The specified luminous flux values may vary by %10.

ORDER CODE EXPANSION

OF10- 0120 - 040 - 7 40 S - 9005-0120- 0 S S S 65

GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
OF10	020S 030M 040L 05XL	030: 30W 050: 50W 070: 70W 100: 100W 150: 150W 200: 200W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K MB: Amber RD: Red GR: Green BL: Blue	S: Standart	9005: Black	0120: 120°	0: ON-OFF I: IR Sens.	S: LAMPTIME	S: Standart	S: Standart	65: IP65