



Indirect Recessed Backlight LED Lighting 60x60

Housing
Elektrostatik toz boyalı DKP Metal Housing

Diffuser
Opal diffuser with high transmissivity.

LED
SMD LED with high color rendering index
minimum lifetime of 100.000 hours (L70-85°C).

Driver
Constant current output, high efficiency driver.

Option
► Emergency Lighting Kit for 1 or 3 hours period.
► DIM/DALI DIM

Housing Color



Light Angle



Light Color



| Product Name | Order Code ⁽²⁾ | CCT (K) | Luminous Flux ⁽¹⁾ | Power | Montage Dimens. | Voltage | Weight | Measurements |
|-----------------------------|---------------------------|---------|------------------------------|-------|-----------------|---------|---------|--------------|
| Indirect Recessed Backlight | 205320 | 3000K | 1860 lm | 36W | 575x575mm | 220VAC | 4,40 Kg | |
| Indirect Recessed Backlight | 205420 | 4000K | 1950 lm | | | | | |
| Indirect Recessed Backlight | 205620 | 6500K | 2050 lm | | | | | |

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X= 0 White Y= 3 3000K
2 Grey 4 4000K
3 Black 6 6500K