

Clip-in Backlight LED Lighting 60x60

Housing
Eletrostatic powder paint DKP Metal Housing

Diffuser
Opal diffuser with high transmissivity.

LED
SMD LED with high color rendering index
minimum lifetime of 100.000 hours (L70-85°C).

Driver
Constant current output, high efficiency driver.

Option
► Emergency Lighting Kit for 1 or 3 hours period.
► DIM/DALI DIM


Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Montage Dimens.	Voltage	Weight	Measurements
Recessed Clip-In Backlight	212321	3000K	1565 lm	36W	600x600mm	220VAC	4,00 Kg	
Recessed Clip-In Backlight	212421	4000K	1640 lm					
Recessed Clip-In Backlight	212621	6500K	1725 lm					
Recessed Clip-In Backlight	213321	3000K	1860 lm	36W	600x600mm	220VAC	3,70 Kg	
Recessed Clip-In Backlight	213421	4000K	1950 lm					
Recessed Clip-In Backlight	213621	6500K	2050 lm					

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X=0 White Y=3 3000K
2 Grey 4 4000K
3 Black 6 6500K