



Clip-in Slim LED Lighting 60x60

Housing
Electrostatic powder paint DKP Metal Housing.

LGP
LGP with high reflection.


Diffuser
Opal diffuser with high transmissivity.

LED
SMD LED with high color rendering index
minimum lifetime of 50.000 hours (L70-85°C).

Driver
Constant current output, high efficiency driver.

Option
► Emergency lighting kit for 1 or 3 hours period.
► DIM/DALI DIM

Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Montage Dimens.	Voltage	Weight	Measurements
Recessed Slim Clip-In	260384	3000K	2700 lm	40W	600X600mm	220VAC	2,93 Kg	
Recessed Slim Clip-In	260484	4000K	2850 lm					
Recessed Slim Clip-In	260684	6500K	3000 lm					
Recessed Slim Clip-In	260385	3000K	3175 lm	48W	600X600mm	220VAC	2,93 Kg	
Recessed Slim Clip-In	260485	4000K	3430 lm					
Recessed Slim Clip-In	260685	6500K	3630 lm					

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X= 0 White Y= 3 3000K
2 Grey 4 4000K
3 Black 6 6500K



Clip-in Slim LED Lighting 30x30 - 30x60 - 30X120

Housing
Electrostatic powder paint DKP Metal Housing.

LGP
LGP with high reflection.

Diffuser
Opal diffuser with high transmissivity.

LED
SMD LED with high color rendering index
minimum lifetime of 50.000 hours (L70-85°C).

Driver
Constant current output, high efficiency driver.

Option
► Emergency lighting kit for 1 or 3 hours period.
► DIM/DALI DIM

Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Montage Dimens.	Voltage	Weight	Measurements
Recessed Slim Clip-In 30x30	260381	3000K	650 lm	12W	300X300mm	220VAC	0,95 Kg	
Recessed Slim Clip-In 30x30	260481	4000K	750 lm					
Recessed Slim Clip-In 30x30	260681	6500K	850 lm					
Recessed Slim Clip-In 30x60	260382	3000K	1350 lm	20W	600x600mm	220VAC	1,84 Kg	
Recessed Slim Clip-In 30x60	260482	4000K	1400 lm					
Recessed Slim Clip-In 30x60	260682	6500K	1550 lm					
Recessed Slim Clip-In 30x120	260383	3000K	2900 lm	40W	300X1200mm	220VAC	2,70 Kg	
Recessed Slim Clip-In 30x120	260483	4000K	3000 lm					
Recessed Slim Clip-In 30x120	260683	6500K	3100 lm					

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X=0 White Y=3 3000K
2 Grey 4 4000K
3 Black 6 6500K



Decorative Clip-in Slim LED Lighting 60x60

Housing
Electrostatic powder paint DKP Metal Housing.

LGP
LGP with high reflection.

Diffuser
Opal diffuser with high transmissivity.

LED
SMD LED with high color rendering index minimum lifetime of 50.000 hours (L70-85°C).

Driver
Constant current output, high efficiency driver.

Option
► Emergency lighting kit for 1 or 3 hours period.
► DIM/DALI DIM


Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Power	Montaj Ölçüsü	Voltage	Weight	Measurements
Decorative Recessed Slim Clip-in	269384	3000K	40W	600x600mm	220VAC	2,73 Kg	 600mm
Decorative Recessed Slim Clip-in	269484	4000K					
Decorative Recessed Slim Clip-in	269684	6500K					
Decorative Recessed Slim Clip-in	269385	3000K	48W	600x600mm	220VAC	2,93 Kg	 600mm
Decorative Recessed Slim Clip-in	269485	4000K					
Decorative Recessed Slim Clip-in	269685	6500K					

(1) 32XY42 X=0 White Y=3 3000K
2 Grey 4 4000K
3 Black 6 6500K