



21XX30



21XX32



With Lens Recessed Backlight LED Lighting 60x60

Housing

Eletrostatic powder paint DKP Metal Housing

Diffuser

Opal diffuser with high transmissivity.

LED

SMD LED with high color rendering index
minimum lifetime of 100.000 hours (L70-85°C).

Driver

Constant current output, high efficiency driver.

Option

- Emergency Lighting Kit for 1 or 3 hours period.
- DIM/DALI DIM


Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Montage Dimens.	Voltage	Weight	Measurements
With Lens Recessed Backlight	212332	3000K	3800 lm	40W	555x555mm	220VAC	2,68 Kg	
With Lens Recessed Backlight	212432	4000K	4000 lm					
With Lens Recessed Backlight	212632	6500K	4200 lm					
With Lens Recessed Backlight	212330	3000K	3250 lm	40W	555x555mm	220VAC	2,68 Kg	
With Lens Recessed Backlight	212430	4000K	3450 lm					
With Lens Recessed Backlight	212630	6500K	3600 lm					

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X= 0 White Y= 3 3000K
2 Grey 4 4000K
3 Black 6 6500K